


- ☐ Neues Anchor Plugin hinzufügen (zugewiesen an [Michael Schlenstedt](#))
- ☐ Neues Markdown Plugin hinzufügen (zugewiesen an [Michael Schlenstedt](#))


# Syntax

[DokuWiki](#) zeichnet sich u. a. durch einfache Textformatierungen aus. Dadurch bleiben die Dateien, die den Inhalt enthalten, gut lesbar. In den nachfolgenden Abschnitten sind die möglichen Formatierungsarten aufgelistet, die innerhalb des Editors verwendet werden können. Einige der hier vorgestellten Formatierungen sind auch direkt über die  [Quickbuttons](#) erreichbar. Ein erstes Beispiel, wie der Aufbau einer Seite aussehen kann, findest du, wenn du dir diese Seite im Quelltext-Modus anzeigen lässt. Klicke dazu auf den Button "Vorschau".

Zum Ausprobieren oder Üben kann die [Spielwiese](#) verwendet werden.

## 1 Texte

### 1.1 Formatierungen

DokuWiki unterstützt **fetten**, *kursiven*, unterstrichenen und dicktengleichen ( [Dichte](#)) Text. Natürlich kann auch alles ***kombiniert*** werden.

```
DokuWiki unterstützt **fetten**, //kursiven//, __unterstrichenen__ und  
'dicktengleichen' Text.  
Natürlich kann auch alles **__/'kombiniert'/'__** werden.
```

Ebenso gibt es <sub>tiefgestellten</sub> und <sup>hochgestellten</sup> Text.

```
Ebenso gibt es <sub>tiefgestellten</sub> und <sup>hochgestellten</sup> Text.
```

Text kann als ~~gelöscht<sup>1)</sup>~~ markiert werden.

```
Text kann als <del>gelöscht</del> markiert werden.
```

### 1.2 Absätze

Ein Absatz wird durch eine leere Zeile erzeugt. Eine neue Zeile (Zeilenumbruch) kann durch zwei "Backslashes" (umgekehrte Schrägstriche: \) gefolgt von einem Leerzeichen erzeugt werden.

Dies ist ein Beispielttext mit einigen Zeilenumbrüchen.

Beachte: Die zwei umgekehrten Schrägstriche werden nur erkannt, wenn sie am Zeilenende stehen oder wenn ihnen ein Leerzeichen folgt.

So\\sieht es ohne Leerzeichen aus.

```
Dies ist ein Beispieltext mit einigen Zeilenumbrüchen.\\ Beachte: Die zwei
umgekehrten Schrägstriche
werden nur erkannt, wenn sie am Zeilenende stehen\\
oder wenn ihnen ein\\ Leerzeichen folgt.\\ So\\sieht es ohne Leerzeichen
aus.
```

Zeilenumbrüche durch zwei "Backslashes" (umgekehrte Schrägstriche: \\) sollten nur verwendet werden, wenn sie unbedingt notwendig sind.

## 1.3 Überschriften

Mit fünf unterschiedlichen Ebenen, getrennt durch Überschriften, kann der Inhalt einer Seite strukturiert werden. Die Überschriften werden mit maximal sechs "=" eingerahmt, je nach Größe. H1 ist die Überschrift auf höchster Ebene. Am einfachsten ist es zur Erzeugung der Überschriften, die Symbolleiste zu verwenden. Das Einfügen der Überschriften erfolgt über die Buttons, die ein "H" anzeigen.

Es ist sinnvoll, wenn immer eine Level 1 Überschrift am Anfang eines Artikels steht.

Wenn in einer Seite mehr als drei Überschriften vorkommen, wird automatisch ein Inhaltsverzeichnis erstellt, welches alle Überschriften auflistet. Soll dieses Inhaltsverzeichnis nicht erstellt werden, muss der Befehl: `~~NOTOC~~` mit in die Seite aufgenommen werden.

```
===== Überschrift Ebene 1 =====
===== Überschrift Ebene 2 =====
==== Überschrift Ebene 3 ====
=== Überschrift Ebene 4 ===
== Überschrift Ebene 5 ==
```

Innerhalb von Überschriften können standardmäßig keine weiteren Formatierungen vorgenommen werden! (s. [FAQ - Headerlinks](#))

## 1.4 unformatierte Abschnitte

Um Text so anzuzeigen, wie er geschrieben wurde, egal ob er DokuWiki Formatierungen oder andere Formatierungen enthält, kann man jede Zeile mit zwei Leerzeichen beginnen (so wie es in dieser Seite angewendet wurde) oder einen der Bezeichner "code" bzw. "file" benutzen:

```
Mit "code": In diesem Text werden keine überflüssigen Leerzeichen entfernt:
wie hier          <-- zwischen
```

```
<file plain Beispiel.txt>
Mit dem Bezeichner "file" kann ein bestimmter Abschnitt als einzelner
Bestandteil
auf einer Seite zum Download angeboten werden.
```

```
</file>
```

Innerhalb von "file" ist auch die im Abschnitt weiter unten beschriebene [Syntax-Hervorhebung](#) aktivierbar.

HelloWorld.pl

```
#!/usr/bin/perl
print "Hello World!\n";
```

```
<file perl HelloWorld.pl>
#!/usr/bin/perl
print "Hello World!\n";
</file>
```

Um jegliche Umwandlung durch DokuWiki abzustellen, umschlieÙe den entsprechenden Bereich mit "nowiki" Bezeichnen oder kürzer mit doppelten Prozentzeichen %%.

Dieser Text enthält Links wie: <http://www.splitbrain.org> und **\*\*Formatierungen\*\*** aber sie werden nicht umgesetzt und erscheinen als normaler Text.

Dieser Text ist nun mit %% markiert und hat die gleiche Wirkung wie "nowiki". "Dieser Text enthält links wie: <http://www.splitbrain.org> und **\*\*Formatierungen\*\*** aber sie werden nicht umgesetzt und erscheinen als normaler Text."

Einfach den Quelltext dieser Seite anschauen (den Knopf "Edit" drücken) um zu sehen, wie diese Blöcke angewendet werden.

## 1.5 Syntax-Hervorhebung

[DokuWiki](#) kennt Syntax-Highlighting für Quellcode, um dessen Lesbarkeit zu erhöhen. Dafür wird [GeSHi](#) "**G**eneric **S**yntax **H**ighlighter" benutzt. Somit wird jede Programmiersprache unterstützt, die GeSHi kennt. Es wird der gleiche Bezeichner wie im vorherigen Abschnitt benutzt, nur dass er nun auch den Namen der Sprache enthält: `<code java> Quelltext </code>`

```
/**
 * The HelloWorldApp class implements an application that
 * simply displays "Hello World!" to the standard output.
 */
class HelloWorldApp {
    public static void main(String[] args) {
        System.out.println("Hello World!"); //Display the string.
    }
}
```

Es werden folgende Sprachen unterstützt: *actionscript, actionscript-french, ada, apache, applescript, asm, asp, bash, caddcl, cadlisp, c, c\_mac, cpp, csharp, css, delphi, diff, d, div, dos, eiffel, freebasic, gml, html4strict, ini, inno, java, javascript, lisp, lua, matlab, mpasm, nsis, objc, ocaml, ocaml-brief,*

*oobas, oracle8, pascal, perl, php-brief, **php**, python, qbasic, scheme, sdlbasic, smarty, **sql**, ruby, vb, vbnet, vhd, visualfoxpro, **xml***

## 1.6 Zitat / Kommentar

Um einen Text als Zitat oder Kommentar zu kennzeichnen, wird das "größer als" - Zeichen folgendermaßen verwendet:

```
Ich denke wir sollten es tun.  
  
> Nein, sollten wir nicht.  
  
>> Doch!  
  
> Wirklich?  
  
>> Ja!  
  
>>> Dann lass es uns tun!  
  
>>> Kommentare oder Zitate können auch über mehrere Zeilen gehen, wie dieser  
völlig unsinnige Text zeigt. Um einen Text als Zitat oder Kommentar zu  
kennzeichnen, wird das "größer als"-Zeichen folgendermaßen verwendet
```

Ich denke wir sollten es tun

Nein, sollten wir nicht.

Doch!

Wirklich?

Ja!

Dann lass es uns tun

Kommentare oder Zitate können auch über mehrere Zeilen gehen, wie dieser völlig unsinnige Text zeigt. Um einen Text als Zitat oder Kommentar zu kennzeichnen, wird das "größer als"-Zeichen folgendermaßen verwendet

## 1.7 Escapezeichen

Will man verhindern, dass DokuWiki irgendwelche Formatierungen am bzw. Umwandlungen im Text vornimmt so kann man die Prozentzeichen benutzen

```
%[ [wiki:testseite|Testseite] ]%%
```

Die Ausgabe würde dann folgendermaßen aussehen `[[wiki:testseite|Testseite]]`

## 1.8 Fußnoten

Fußnoten <sup>2)</sup> werden durch eine doppelte runde Klammer dargestellt <sup>3)</sup>. Der Text zwischen den Klammern wird an das Ende der Seite geschrieben. Die Reihenfolge und somit die Nummerierung übernimmt DokuWiki.

```
Fußnoten ((dies ist eine Fußnote)) werden durch eine doppelte runde Klammer dargestellt ((eine zweite Fußnote))
```

## 1.9 Linien

Durch vier oder mehr Bindestriche bzw. Minuszeichen "-" wird eine horizontale Linie erzeugt:

# 2 Links

Mit DokuWiki können fünf unterschiedliche Arten von Links benutzt werden:

## 2.1 Extern

Externe Links (Verweise auf andere Webseiten oder Dateien) werden automatisch erkannt: <http://www.google.com> oder einfach [www.google.com](http://www.google.com). Verweise können auch hinter eigenen Begriffen versteckt werden: [hier ist google](#). E-Mail Adressen werden in spitze Klammern gesetzt: [andi@splitbrain.org](mailto:andi@splitbrain.org).

```
Externe Links werden automatisch erkannt: http://www.google.com oder einfach www.google.com.
```

```
Verweise können auch hinter eigenen Begriffen versteckt werden:
```

```
[[http://www.google.com|hier ist google]].
```

```
E-Mail Adressen werden in spitze Klammern gesetzt: <andi@splitbrain.org>.
```

## 2.2 Intern

Interne Links, also Verweise auf Seiten innerhalb von DokuWiki, werden in doppelten eckigen Klammern gesetzt ("Alt Gr+8" bzw. Alt Gr+9 unter Windows bzw. Wahl taste+5 und Wahl taste+6 bei Apple-Betriebssystemen): [📄 pagename](#)

Ein Link kann auch hinter einem Begriff oder einer Beschreibung versteckt werden: [Beschreibung für](#)

einen Link.

Interne Links werden in doppelten eckigen Klammern gesetzt:  
`[[pagename]]`

Ein Link kann auch hinter einem Begriff oder einer Beschreibung versteckt werden:  
`[[pagename|Beschreibung für einen Link]]`.

Dateinamen für neue Seiten im Wiki werden automatisch in Kleinbuchstaben umgewandelt! Umlaute sind genauso wie Sonderzeichen nicht erlaubt!

Durch einen Doppelpunkt werden Namensbereiche im Wiki aufgelöst: [namespaces](#)

Durch einen Doppelpunkt werden Namensbereiche im Wiki aufgelöst: `[[de:namespaces]]`

Weitere Informationen zu Namensbereichen: [📖 de:namespaces](#).

Die Verlinkung zu einem speziellen Abschnitt innerhalb des Dokuments (Anker) ist auch möglich. Der Abschnittsname wird getrennt durch ein Doppelkreuz (#) an den Seitennamen gehängt.

Dieses Beispiel verlinkt zu [diesem Abschnitt](#).

Dieses Beispiel verlinkt zu `[[de:wiki:syntax#intern|diesem Abschnitt]]`.

Anmerkungen:

- Links zu [existierenden Seiten](#) werden anders angezeigt als Links zu [nicht-existierenden](#) Seiten.
- DokuWiki verwendet standardmäßig keine [📖 CamelCase](#) für Links. In der Einstellungsdatei: [📖 config](#) kann das aber geändert werden. **Hinweis:** wenn das Wort "DokuWiki" als Link angezeigt wird, dann ist diese Option eingeschaltet.
- Ändert sich eine Überschrift im Zieldokument, führt der Anker ins Leere ohne dass der Link dabei als fehlerhaft angezeigt wird.
- Anker werden klein geschrieben, es werden Leerzeichen mit Unterstrichen und Umlaute mit ihren Umschreibungen (ä = ae) verwendet.

## 2.3 Interwiki

DokuWiki unterstützt auch Links in andere Wikis, sogenannte [📖 de:interwiki](#) Links. Ein Link zur Wikipedia Seite über Wikis: [📖 Wiki](#)

DokuWiki unterstützt auch Links in andere Wikis, sogenannte `[[doku>de:interwiki]]` Links.  
Ein Link zur Wikipedia Seite über Wikis: `[[wpde>Wiki]]`

## 2.4 Windows-Freigaben

DokuWiki kennt auch Links auf Windows-Freigaben: [freigegebener-Ordner](#). Dies ist allerdings nur in einer homogenen Benutzergruppe sinnvoll (siehe [Intranet](#)).

```
[[\\server\freigabe|this]].
```

Hinweis:

- Aus Sicherheitsgründen funktioniert direktes Navigieren durch die Freigaben standardmäßig nur mit dem Internet Explorer (und das nur in der "lokalen Zone")!
- Für Mozilla und Firefox kann es durch die Option [security.checkloaduri](#) eingeschaltet werden, was aber nicht empfohlen wird! (Weitere Informationen: [Links to local pages do not work](#))
- Opera ignoriert als Sicherheitsfeature seit [Version 7.54](#) alle Links auf *file:* in Webseiten.
- Für weitere Informationen siehe: 151

## 2.5 Bilder als Links

Bilder können für einen Link auf eine interne oder externe Datei verwendet werden. Dazu wird die Syntax zur Anzeige von Links einfach mit der zur Anzeige von Bildern (siehe unten) kombiniert:

```
[[http://www.php.net|{{wiki:dokuwiki-128.png}}]]
```




Bitte beachte: Bildformatierungen sind die einzigen Formatierungen, die in Linknamen benutzt werden können!


## 3 Bilder und andere Dateien

### 3.1 Bilder im DokuWiki speichern

Um Bilder im DokuWiki speichern zu dürfen, muss der Benutzer die entsprechende Berechtigung besitzen ([ACL](#)). Zum Hochladen ist mindestens die Berechtigung "Hochladen" (engl. "Upload"), zum Löschen "Entfernen" (engl. "Delete") für den [Namensraum](#) erforderlich.

## 3.2 Größe von Bildern

Mit geschweiften Klammern können sowohl externe als auch interne  **Bilder** eingebunden werden. Das Bild heißt in diesem Beispiel "dokuwiki-128.png". Optional kann deren Größe angegeben werden:



Originalgröße:	<code>{{wiki:dokuwiki-128.png}}</code>
Eine Breite vorgeben:	<code>{{wiki:dokuwiki-128.png?50}}</code>
Breite und Höhe vorgeben:	<code>{{wiki:dokuwiki-128.png?200x50}}</code>
Größe für externe Bilder vorgeben:	<code>{{http://de3.php.net/images/php.gif?200x50}}</code>

## 3.3 Ausrichten von Bildern

Mit Leerzeichen zur Rechten und/oder Linken innerhalb der Klammern kann ein Bild horizontal ausgerichtet werden (Links, Zentriert, Rechts).







```
{{wiki:dokuwiki-128.png }}
{{ wiki:dokuwiki-128.png }}
{{ wiki:dokuwiki-128.png}}
```

Bei Ausrichtung und der Verwendung eines Titels sollte man drauf achten, dass der Titel nach dem Leerzeichen kommt:

```
{{wiki:dokuwiki-128.png |Linksbündig}}
{{ wiki:dokuwiki-128.png |Zentriert }}
{{ wiki:dokuwiki-128.png|Rechtsbündig}}
```

## 3.4 Tooltips

Auch Titel, in den meisten Browsern als Tooltip angezeigt, können angegeben werden.



```
{{ wiki:dokuwiki-128.png |Dies ist ein Titel}}
```


## 3.5 Dateidownload

Wenn eine Datei angegeben wird, die kein Bild (gif, jpg, png) ist, so wird sie als Link angezeigt und so zum Download angeboten.

Beispiel

```
{{ wiki:dokuwiki-128.txt |Beispiel}}
```

## 3.6 Automatische Verlinkung

Bilder werden automatisch mit einer Verlinkung zur Ihren  [Metadaten](#) erstellt - Bsp.: 

Dieses Verhalten kann über die Option ?nolink<sup>4)</sup> unterbunden werden<sup>5)</sup>:



```
{{wiki:dokuwiki-128.png?15&nolink}}
```

Außerdem kann mit ?direct das Bild, z.Bsp. als Vollansicht, direkt verlinkt werden:



```
{{wiki:dokuwiki-128.png?15&direct}}
```

## 4 Listen

DokuWiki kennt unsortierte und nummerierte Listen. Um einen Listeneintrag zu erzeugen, beginne eine Zeile mit zwei Leerzeichen. Diesen Leerzeichen folgt dann ein "\*" für unsortierte oder ein "-" für nummerierte Listen.

- Dies ist ein Eintrag einer unsortierten Liste
  - Ein zweiter Eintrag
    - Unterschiedliche Ebenen einer Liste durch Hinzufügen von weiteren zwei Leerzeichen
  - Noch ein Eintrag
1. Dies ist ein Eintrag einer nummerierten Liste
  2. Ein zweiter Eintrag
    1. Unterschiedliche Ebenen einer Liste durch Hinzufügen von weiteren zwei Leerzeichen
  3. Noch ein Eintrag

```
* Dies ist ein Eintrag einer unsortierten Liste
* Ein zweiter Eintrag
  * Unterschiedliche Ebenen einer Liste durch Hinzufügen von weiteren zwei
Leerzeichen
* Noch ein Eintrag

- Dies ist ein Eintrag einer nummerierten Liste
- Ein zweiter Eintrag
  - Unterschiedliche Ebenen einer Liste durch Hinzufügen von weiteren zwei
Leerzeichen
- Noch ein Eintrag
```

## 5 Tabellen

### 5.1 Grundlegender Aufbau

Mit DokuWiki können Tabellen ganz einfach erstellt werden:

<b>hervorgehoben</b>	<b>zum Beispiel für</b>	<b>eine Titelzeile</b>
Zeile 1 Spalte 1	Zeile 1 Spalte 2	Zeile 1 Spalte 3
Zeile 2 Spalte 1	doppelte Spaltenbreite (beachte den doppelten senkrechten Strich)	
Zeile 3 Spalte 1	Zeile 2 Spalte 2	Zeile 2 Spalte 3
Zeile 4 Spalte 1		Zeile 4 Spalte 3

Felder einer Tabelle starten mit "|" für ein normales Feld oder mit einem "^" für hervorgehobenes Feld.

```

^ hervorgehoben      ^ zum Beispiel für
^ eine Titelzeile    ^
| Zeile 1 Spalte 1   | Zeile 1 Spalte 2
| Zeile 1 Spalte 3   |
| Zeile 2 Spalte 1   | doppelte Spaltenbreite (beachte den doppelten
senkrechten Strich) ||
| Zeile 3 Spalte 1   | Zeile 2 Spalte 2
| Zeile 2 Spalte 3   |

```

## 5.2 Formatierung/Ausrichtung

### Leerzellen

Zellen über mehrere Spalten werden erzeugt wenn man, wie oben gezeigt, am Ende einer solchen Spalte so viele "|" oder "^" ohne Leerzeichen dazwischen hintereinander setzt, wie Spalten überbrückt werden sollen. Kurz gesagt: Alle Zeilen einer Tabelle müssen die gleiche Anzahl an Feldtrennern "|" oder "^" haben.

Hervorgehobene Felder in Vertikaler Ausrichtung sind auch möglich.

	<b>hervorgehoben 1</b>	<b>hervorgehoben 2</b>
<b>hervorgehoben 3</b>	Zeile 1 Spalte 2	Zeile 1 Spalte 3
<b>hervorgehoben 4</b>	Zeile 2 Spalte 2	
<b>hervorgehoben 5</b>	Zeile 3 Spalte 2	Zeile 3 Spalte 3

Wie wir sehen, entscheidet der Feldtrenner ("|" oder "^") vor einer Zelle über ihr Aussehen:

```

|      ^ hervorgehoben 1      ^ hervorgehoben 2      ^
^ hervorgehoben 3  | Zeile 1 Spalte 2  | Zeile 1 Spalte 3  |
^ hervorgehoben 4  | Zeile 2 Spalte 2  |      |      |
^ hervorgehoben 5  | Zeile 3 Spalte 2  | Zeile 3 Spalte 3  |

```

### Zellen verbinden

Felder über mehrere Zeilen (**vertikal verbundene Zellen**) lassen sich durch hinzufügen von ":::" in der zu verbindenden Zelle zusammenfügen.



Zum Stand der *Release 2015-08-10a "Detritus"* können Zellen der ersten Zeile nicht in vertikal verbundene Zellen einbezogen werden.

Titelzeile 1	Titelzeile 2	Titelzeile 3
Zeile 1 Spalte 1	Diese Zelle ist vertikal verbunden	Zeile 1 Spalte 3
Zeile 2 Spalte 1		Zeile 2 Spalte 3
Zeile 3 Spalte 1		Zeile 3 Spalte 3

Außer den drei Doppelpunkten darf die zu verbindende Zelle keine weiteren Inhalte haben.

```
^ Titelzeile 1          ^ Titelzeile 2                      ^ Titelzeile 3
^
| Zeile 1 Spalte 1      | Diese Zelle ist vertikal verbunden | Zeile 1 Spalte
3                        |
| Zeile 2 Spalte 1      | :::                                | Zeile 2 Spalte
3                        |
| Zeile 3 Spalte 1      | :::                                | Zeile 3 Spalte
3                        |
```

Felder über mehrere Spalten (**horizontal verbundene Zellen**) lassen sich durch hinzufügen von ^ bzw. | in der zu verbindenden Zelle zusammenfügen.

Titelzeile 1	Titelzeile 2	Titelzeile 3
Zeile 1 Spalte 1	Diese Zelle ist horizontal verbunden	
Zeile 2 Spalte 1	Zeile 2 Spalte 2	Zeile 2 Spalte 3
Zeile 3 Spalte 1	Zeile 3 Spalte 2	Zeile 3 Spalte 3

```
^ Titelzeile 1          ^ Titelzeile 2                      ^ Titelzeile 3
^
| Zeile 1 Spalte 1      | Diese Zelle ist horizontal verbunden
||
| Zeile 2 Spalte 1      | Zeile 2 Spalte 2                      | Zeile 2
Spalte 3                |
| Zeile 3 Spalte 1      | Zeile 3 Spalte 2                      | Zeile 3 Spalte
3                        |
```

Textausrichtung

Der Inhalt einer Zelle kann horizontal innerhalb der Zelle ausgerichtet werden:

- Rechtsbündig - zwei Leerzeichen links vom Text
- Linksbündig - Leerzeichen rechts vom Text
- Zentriert - zwei Leerzeichen links und rechts vom Text

Tabelle mit Ausrichtung		
Rechts	Mitte	Links
Links	Rechts	Mitte
XXXXXXXXXXXXXX	XXXXXXXXXXXXXX	XXXXXXXXXXXXXX

So sieht die Formatierung aus:

```

^           Tabelle mit Ausrichtung           ^^^
|           Rechts|           Mitte           |Links           |
|Links           |           Rechts|           Mitte           |
| xxxxxxxxxxxxxx | xxxxxxxxxxxxxx | xxxxxxxxxxxxxx |

```

Hinweis zu dem senkrechten Balken-Zeichen: dieses Zeichen ist auf einer PC-Tastatur erreichbar über die Taste "<" bei zusätzlich gedrückter "AltGr"-Taste. Ist dort auch aufgedruckt. Apple-Nutzer erreichen das Zeichen mit der Wahl taste ("Alt") und der "7".

## 6 sonstige Formatierungen

### 6.1 horizontale Linie

Mit vier aufeinander folgenden Minuszeichen (alleine in einer Zeile) kann eine horizontale Linie erzeugt werden:

----

### 6.2 Smileys

DokuWiki verwandelt oft genutzte [Emoticons](#) zu kleinen Smiley-Grafiken. Weitere Smiley-Grafiken können im Ordner "smily" abgelegt und dann in der Datei `conf/smileys.conf` bzw. für benutzereigene Smileys unter `conf/smileys.local.conf` eingetragen werden. Hier ist nun eine Übersicht der standardmäßig in DokuWiki enthaltenen Smileys:



### 6.3 Typografie

[DokuWiki](#) kann einfache Textzeichen in ihre typografischen Entsprechungen umwandeln. Hier eine Liste aller Zeichen, die DokuWiki kennt:

→ ← ↔ ⇒ ⇐ ⇔ » « – 640x480 © ™ ® "He thought 'It's a man's world'..."

```

-> <- <-> => <=> <=> >> << -- --- 640x480 (c) (tm) (r)
"He thought 'It's a man's world'..."

```

Bitte beachtet: Diese Umwandlungen können in der Konfigurationsdatei abgestellt werden

## 6.4 HTML und PHP einbinden

In einer Seite kann sowohl HTML als auch PHP direkt benutzt werden.

This is some **HTML-Code**

```
<html>
This is some <font color="red" size="+1">HTML-Code</font>
</html>
```

```
<php>
echo 'A logo generated by PHP: ';
echo '';
</php>
```

```
<php>
echo 'A logo generated by PHP: ';
echo '';
</php>
```

**Achtung:** Das Einbinden von HTML und PHP in einer Seite kann in der Konfigurationsdatei ausgeschaltet werden<sup>6)</sup>. Ist diese Option aktiviert, wird der Quellcode dieser Abschnitte als Text angezeigt und nicht ausgeführt.

**Achtung:** Das Einbinden von HTML und PHP auf einer Seite im Internet ist gewöhnlich ein schweres Sicherheitsrisiko! Diese Funktion ist nur für das Intranet gedacht!

## 7 Kontroll-Makros

Einige Syntax-Befehle beeinflussen wie Dokuwiki eine Seite beim Aufruf ausgibt. Die folgenden Kontroll-Makros sind verfügbar:

Makro	Beschreibung
~~NOTOC~~	Wenn dieses Makro in eine Seite eingebunden ist, wird das <a href="#">Table of Content</a> nicht erstellt.
~~NOCACHE~~	Alle Seiten werden aus Performancegründen zwischengespeichert. Unter bestimmten Umständen ist dieses Verhalten aber nicht gewollt. Beim Einfügen dieses Makros wird DokuWiki angewiesen, den Inhalt der Seite neu aufzubauen.

## 8 Syntax-Plugins

Die Syntax von DokuWiki kann durch [Plugins](#) erweitert werden. Wie die einzelnen Plugins benutzt

werden, findet ihr in den folgenden Kapiteln. Die folgenden Plugins sind auf dieser DokuWiki Installation verfügbar:

Folded Plugin

Full documentation: <https://www.dokuwiki.org/plugin:folded>

If you want to make additional information available that is hidden by default, you have two options with this plugin:

Inline:

This is example ++text | with some of it only shown when you unfold it++. And after that the text just continues to flow in the same paragraph.

This is example [text](#) with some of it only shown when you unfold it. And after that the text just continues to flow in the same paragraph.

Block:

This is example text.

++++ Title |

| This table | is only shown | when you unfold the block |

{{page>some other wiki page&inline}}

++++

	Inline	Block
Syntax	++title  formatted text ++	++++title  any content +++++
HTML	<span> tag	<div> tag
Can contain formatting	😊	😊
Can contain block elements <sup>7)</sup>	—	😊
Can be used within a paragraph, table, list, etc.	😊	—

You can see in the image below.



**Note: As of version 2005-09-02 the syntax has changed to allow linked titles to unfold and fold the section. The pipe char between title and text is mandatory.**

## Wrap Plugin

Full documentation: <https://www.dokuwiki.org/plugin:wrap>

This plugin gives you the ability to wrap wiki text inside containers (divs or spans) and give them

1. a certain class (with loads of useful preset classes)
2. a width
3. a language with its associated text direction

Basic Syntax:

```
<WRAP classes #id width :language>
"big" content
</WRAP>
```

**\*\*or\*\***

```
<block classes #id width :language>
"big" content
</block>
```

**or**

```
<div classes #id width :language>
"big" content
</div>
```

An uppercase **<WRAP>** (or alternatively **<block>** or **<div>**) creates a **div** and should be used for **"big"** containers, **surrounding** paragraphs, lists, tables, etc.

```
<wrap classes #id width :language>"small" content</wrap>

or

<inline classes #id width :language>"small" content</inline>

or

<span classes #id width :language>"small" content</span>
```

A lowercase **<wrap>** (or alternatively **<inline>** or **<span>**) creates a **span** and should be used for **"small"** containers, **inside** paragraphs, lists, tables, etc.

Since version 2013-06-13 there is also a shorthand syntax (for wraps without content):

```
<WRAP classes #id /> or <block classes #id /> or <div classes #id />
```

and

```
<wrap classes #id /> or <inline classes #id /> or <span classes #id />
```



Please note, some things **won't work with spans: alignments** (including alignments



generated by changing the text direction), **multi-columns** and **widths** if the according wrap isn't floated as well.



## Examples

The plugin comes with an example page, which should explain a lot and looks like this in the default template, see <https://demo.selfthinker.org/plugin:wrap>

## Classes

The following classes are currently available:



class name	description/notes
<b>columns</b> - similar to <b>columns</b> , <b>side_note</b> , <b>styler</b> , <b>tip</b>	
<b>column</b>	same as <code>left</code> in LTR languages and same as <code>right</code> in RTL languages
<b>left</b>	same as <code>column</code> , will let you float your container on the left
<b>right</b>	will let the container float right
<b>center</b>	will position the container in the horizontal center of the page
<b>col2..col5</b>	will show the text in multiple columns determined by their amount (2, 3, 4 or 5), only works in modern browsers (no IE9 and below)
<b>colsmall</b> , <b>colmedium</b> , <b>collarge</b>	will also show the text in multiple columns but determined by their width (small, medium or large), only works in modern browsers (no IE9 and below)
<b>widths</b> -  <b>experimental, might not work as expected, includes mobile support</b>	
<b>half</b>	fits two columns in a row, should be used in pairs
<b>third</b>	fits three or two columns in a row, should be used in triplets or together with <code>twothirds</code>
<b>twothirds</b>	fits two columns in a row when used together with <code>third</code> , one 1/3 wide and another 2/3 wide
<b>quarter</b>	fits four columns in a row, should be used in quads
<b>alignments</b> - similar to <b>divalign</b> , <b>columns</b> , <b>styler</b> -  <b>don't work with spans!</b>	
<b>leftalign</b>	aligns text on the left
<b>rightalign</b>	aligns text on the right
<b>centeralign</b>	centers the text
<b>justify</b>	justifies the text
<b>boxes and notes</b> - similar to <b>box</b> , <b>note</b> , <b>tip</b>	
<b>box</b>	creates a box around the container (uses colours from <code>style.ini</code> )
<b>info</b> (was information in first version)	creates a blue box with an info icon
<b>important</b>	creates an orange box with an important icon

class name	description/notes
<b>alert</b> (  was warning in previous versions)	creates a red box with an alert icon
<b>tip</b>	creates a yellow box with a tip icon
<b>help</b>	creates a violet box with a help icon
<b>todo</b>	creates a cyan box with an todo icon
<b>download</b>	creates a green box with a download icon
<b>round</b>	adds rounded corners to any container with a background colour or a border (only works in modern browsers, i.e. no IE)
<b>danger</b>	creates a red danger safety note
<b>warning</b>	creates an orange warning safety note
<b>caution</b>	creates a yellow caution safety note
<b>notice</b>	creates a blue notice safety note
<b>safety</b>	creates a green safety note
<b>marks</b> - similar to <a href="#">emphasis</a> , <a href="#">important_paragraph</a> , <a href="#">importanttext</a>	
<b>hi</b>	marks text as highlighted
<b>lo</b>	marks text as less significant
<b>em</b>	marks text as especially emphasised
<b>miscellaneous</b>	
<b>clear</b>	similar to <a href="#">clearfloat</a> , should preferably be used with divs, i.e. uppercase <WRAP>s
<b>tabs</b>	if wrapped around a list of links, will show those as tabs
<b>hide</b>	hides the text per CSS (the text will still appear in the source code, in non-modern browsers and is searchable)
<b>noprint</b>	displays text on the screen, but not in print, similar to <a href="#">noprint</a>
<b>onlyprint</b>	displays text only in print, but not on the screen
<b>pagebreak</b>	forces a new page in printouts (not visible on the screen), similar to <a href="#">pagebreak</a>
<b>nopagebreak</b>	tries to avoid a pagebreak in printouts (not visible on the screen)
<b>spoiler</b>	shows white text on a white background, only to be revealed by highlighting it; similar to <a href="#">hide</a>
<b>button</b>	when wrapped around a link, styles it like a button
<b>tablewidth</b>	sets widths of tables inside to whichever width the wrap gets, partly replaces <a href="#">tablewidth</a>
<b>indent</b>	indents the text, could be used instead of <a href="#">tab</a>
<b>outdent</b>	"outdents" the text, could partly be used instead of <a href="#">outdent</a>
<b>prewrap</b>	wraps text inside pre-formatted code blocks, similar to <a href="#">wpre</a>

## Widths

You can set any valid widths on any uppercase <WRAP> container: %, px, em, rem, ex, ch, vw, vh, pt, pc, cm, mm, in. Just set the width before or after or with the classes, e.g.

```
<WRAP someclass 50% anotherclass>...
```

All except percentages will be reduced to have the maximum width available on smaller screens.

You can also use the width keywords `half`, `third`, `twothirds` and `quarter`. To work correctly they need another wrap around them. E.g.

```
<WRAP group>
  <WRAP half column>...</WRAP>
  <WRAP half column>...</WRAP>
</WRAP>
```

will result in two columns next to each other, which will wrap underneath each other on smaller screens and mobile devices.

## Anchor

To define an anchor, the following syntax applies:

```
<wrap #ankername />
```

The anchor is accessible via: `#ankername`

## Languages and Text Directions

You can change the language and the direction of a container by simply adding a colon followed by the language code, like this:

```
<wrap :en>This text is explicitly marked as English.</wrap>
```

The text direction (`rtl`, right to left or `ltr`, left to right) will get inserted automatically and is solely dependent on the language. The list of currently supported languages is taken from:

[http://meta.wikimedia.org/wiki/Template:List\\_of\\_language\\_names\\_ordered\\_by\\_code](http://meta.wikimedia.org/wiki/Template:List_of_language_names_ordered_by_code)

If you like to mark a text with a different text direction than the default one, you should use `divs`, i.e. uppercase `<WRAP>s`. Otherwise the text alignment won't change as well.

This makes it a better replacement of `ltr` (and `lang`).

## Indexmenu Plugin

Full documentation: <https://www.dokuwiki.org/plugin:indexmenu>

This plugin allows you to insert a fully customizable index or a list of pages starting from a specified namespace. It should be useful in DokuWiki sites where pages are organized by [namespaces](#). Main features are:

- Fully customizable with a lot of [flexible options](#), but easy to use and configure for standard needs.
- Built-in support of Navigation features like highlighting the current location or dynamically displaying the tree of the current namespace.

- Easily themeable with prebuilt [JavaScript themes](#).
- Assign [Namespaces title and link \(headpages\)](#) to namespaces.
- Sortable by date, title and custom metadata information.
- AJAX support to speed up sites with many pages.
- Customizable [context mouse menu](#) for usual namespace/page actions.
- TOC pages preview.
- [Replace](#) the DokuWiki page index.
- Hide namespaces/pages according to [ACLs](#) and plugin [settings](#).

Minimum syntax:


- `{{indexmenu>.}}`
- `{{indexmenu>:}}`
- `{{indexmenu>|}}`

That means this `{{indexmenu}}` and this `{{indexmenu>}}` do not work.

Basic syntax usage:

Main	Options
<code>{{indexmenu&gt;ns[#n]</code> <small><code>[ns1[#n] ns2[#n] ...]</code></small>	<code>  <small><code>[js[#theme]] [tsort] ...</code></small> <code>}}</code></code>

Arguments inside `[]` parenthesis are optional. The `#` char is always required with related options.



All the syntax options can be easily accessed with the indexmenu picker in the [edit window toolbar](#).

Full syntax



Settings **before the `|`** separator:

Main	Action	Note
<i>ns</i>	<b>Main namespace</b> name. Index starts from here. Syntax complies with DokuWiki <a href="#">namespaces</a> paths.	"." refers to the namespace of the page containing the indexmenu syntax and <b>not</b> to the current DokuWiki namespace context <sup>8)</sup> (see the <b>context</b> option for this feature). ".." or an empty value shows the root site namespace.
<i>#n</i>	<b>n</b> is a number that specifies how many namespace levels to display open under the <b>main namespace</b> .	If it's not defined then the whole tree, till the deeper node, will be open. If <i>0</i> or <i>1</i> it'll display only nodes under the main namespace. For example: "#2" will display "root:myns1:myns2" but will keep myns2 closed thus hiding "root:myns1:myns2:myns3". Optional.
<i>ns1[#n]</i> ... <i>nsn[#n]</i>	A list of <b>optional namespaces</b> inside the <b>main namespace</b> . Every namespace will be opened or closed at the specified <b>n</b> level. Syntax complies with DokuWiki <a href="#">namespaces</a> .	If <b>n</b> is not defined then all namespaces are open, if <i>0</i> they are closed. "." refers to the namespace of the page containing the indexmenu syntax and <b>not</b> to the current DokuWiki namespace context <sup>9)</sup> (see the <b>context</b> option for this feature). ".." or an empty value shows the root site namespace. Optional.

Optional settings **after the "|" separator** (separated by spaces):

Option	Action	Note
<b>js</b> <b>undo: nojs</b>	JavaScript render method: the index is an expandable tree menu. Without the <code>js</code> option DokuWiki's index renderer is used	Without <b><i>n</i></b> , all nodes are open, with it, nodes are open till <b><i>n</i></b> level.
<b>#theme</b> <b>undo: #default</b>	Theme name for indexmenu icons	A theme is a set of icons inside <i>images</i> directory as described in <a href="#">Theme tutorial</a> . Admins can download and share themes in admin panel. It works only in <b><i>js</i></b> e.g. <b><i>js#tango</i></b>
Next options are available with or without <b><i>js</i></b> option.		
<b>navbar</b> <b>undo: nonavbar</b>	The tree opens itself automatically at the current page namespace. Useful in a navigation sidebar.	Without <b><i>js</i></b> option, the indexmenu page is never cached (just like the default DokuWiki index page) and the DokuWiki loading could be slower depending on the amount of child nodes displayed.
<b>context</b> <b>undo: nocontext</b>	<a href="#">Relative <i>main namespace</i></a> and <b><i>optional namespaces</i></b> will refer to the current DokuWiki namespace context <sup>10)</sup> instead of to the namespace of the page containing the indexmenu syntax. Useful in a navigation sidebar.	The indexmenu page is now never cached so the DokuWiki loading could be slower depending on the amount of child nodes displayed (In <b><i>js</i></b> mode, when a lot of nodes are usually displayed, the <i>max</i> option is recommended). It automatically enable the <b><i>nocookie</i></b> option.
<b>tsort</b> <b>undo: notsort</b>	Sort (only) pages by title.	Useful when <a href="#">useheading</a> is on. By default namespaces are <b><i>not</i></b> sorted, you need the <b><i>nsort</i></b> option for this.
<b>dsort</b> <b>undo: nodsort</b>	Sort (only) pages by date creation (first the oldest).	By default namespaces are <b><i>not</i></b> sorted, you need the <b><i>nsort</i></b> option for this.
<b>msort[#meta]</b> <b>undo: nomsort</b>	Sort (only) pages by a custom <a href="#">metadata</a> information. Without the <code>#meta</code> parameter, i.e. <code>msort</code> , it looks for the custom sorting number specified with the <code>{{indexmenu_n&gt;N}}</code> syntax (see the below <a href="#">metadata tag syntax</a> ). With <code>#meta</code> parameter you can refer to the <a href="#">meta data structure</a> (Array values are managed through the ":" separator, for example: <code>msort#date:modified</code> ).	By default, pages without metadata tag are sorted by page name (the default DokuWiki way), but you can override this behaviour adding also the <code>tsort</code> or <code>dsort</code> option in the indexmenu syntax. By default namespaces are <b><i>not</i></b> sorted, you need the <b><i>nsort</i></b> option for this.
<b>hsort</b> <b>undo: nohsort</b>	Sort the headpages as defined by config setting <a href="#">startpage</a> to the top	<code>msort</code> overrules <code>hsort</code>

Option	Action	Note
<b>rsort</b> <b>undo: norsort</b>	Reverse the sorting of pages (change between ascending and descending).	By default namespaces are <b>not</b> sorted, you need the <b>nsort</b> option for this.
<b>nsort</b> <b>undo: nonsort</b>	Also sort namespaces according to page sort options but grouped separately.	To use in <i>addition</i> to the above sort options. tsort, dsort, msort, hsort apply only for namespaces when using <a href="#">headpages</a> . rsort is applicable always together with nsort.
<b>nons</b> <b>undo: ns</b>	Exclude namespaces nodes from index. It shows only the pages.	Without <b>js</b> , the closing <b>n</b> namespace option prevents to display nodes below the <b>n</b> namespace level.
<b>nopg</b> <b>undo: pg</b>	Exclude pages nodes from index. It shows only the namespaces.	All namespace nodes will link to the start pages (as defined by <a href="#">startpage</a> setting)
<b>skipfile[+ =]/regexp/</b>	Skip files matching the regexp.	skipfile+/. ./ skips files defined with this regexp additional to <a href="#">global skip</a> config. skipfile=/. ./ replace the global skip config with regexp from this syntax. See the global config explanation for some regexp <a href="#">examples</a> .
<b>skipns[+ =]/regexp/</b>	Skip namespaces matching the regexp.	Just like skipfile, but <a href="#">namespaces</a> .
Next options are <i>only</i> available with <b>js</b> option.		
<b>max#n[#m]</b> <b>undo: nomax</b>	If initially closed, the node at <b>n</b> level will retrieve all its child nodes through the AJAX mechanism when opened for the first time. Optionally, the nodes after the <b>n</b> level can be retrieved with AJAX every <b>m</b> sublevels instead of in one go.	It affects the server loading and speeds up the loading of pages in DokuWiki with an high amount of pages. It works only in <b>js</b> . Cookie are automatically disabled, just like with <b>nocookie</b> .
<b>maxjs#n</b> <b>undo: nomaxjs</b>	It sets how many js tree levels to render when page loads. Remaining nodes are rendered (slightly slower) only when they are open by users, by <b>optional namespaces</b> option, by cookies or by <b>navbar</b> option.	Default <b>n</b> is 1 so that it will speed up the page loading, above all with an high amount of pages. It affects only the user-client CPU speed, not the webserver load. It works only in <b>js</b>

Option	Action	Note
<b>id#[random ns number]</b> <b>undo: id#random</b>	 <b>Cookie</b> Identifier for a js indexmenu where the previously opened/closed nodes by a user are stored.	Useful when a page is uncached and you like the tree state is stored in cookie. (See <b>nocookie</b> for disabling cookies.) Default the option <i>id#random</i> is active, also when the option is not specified in the syntax. You can apply self a number as unique identifier for your indexmenu ( e.g. <i>id#20</i> ) or let generate a number unique for requested namespace with <i>id#ns</i> . Read the <a href="#">Js does not remember its previous state</a> section. <b>ATTENTION:</b> ID must be unique for every indexmenu in your DokuWiki site or you'll get strange js behaviors. Tree state storage with cookie only in <b>js</b>
<b>nocookie</b> <b>undo: cookie</b>	Disable  <b>cookies</b> . By default js indexmenu remember selected, open and closed nodes by user during navigation. With this option it doesn't remember them and the tree is blocked to its start status.	Tree state storage with cookie only in <b>js</b>
<b>noscroll</b> <b>undo: scroll</b>	Disable the JavaScript scrolling feature when it doesn't fit the container width. It could solve visualization problems.	It works only in <b>js</b>
<b>notoc</b> <b>undo: toc</b>	Disable the TOC-preview feature.	ToC preview only available in <b>js</b>
<b>nomenu</b> <b>undo: menu</b>	Disable the contextmenu feature.	Context menu only available in <b>js</b>

## Examples

A sample of an indexmenu JS index that could be used inside a navigation sidebar. Its initial status is blocked by the nocookie option, so, when the page is reloaded, it doesn't remember the open and closed nodes by the user.:

```
{{indexmenu>..#1|js navbar nocookie}}
```

JS navigation index with "thread" theme where nodes after the third level are retrieved with Ajax every 2 sublevels. Pages are sorted by title and [custom sort](#) number:

```
{{indexmenu>..#1|js#thread navbar max#3#2 tsort msort}}
```

Standard DokuWiki index showing only pages inside wiki:plugins and lower namespaces (max two levels):

```
{{indexmenu>:wiki:plugins#2|nons}}
```

JS tree showing pages and namespaces both sorted by reverse title. For example, if "archive" contains stuff ("news", "oldnews", etc) that you need to quickly organize by time, you could create numbered [headpages](#) for every namespace (i.e renaming "oldnews" in "news 2006", "news" in "news 2010" and so on) and sort them from new to older:

```
{{indexmenu>:archive#1|js tsort nsort rsort}}
```

Standard index showing the tree of the current context <sup>11)</sup> opened at the second level .

```
{{indexmenu>playground#2|context}}
```

Show all current namespace pages .

```
{{indexmenu>.:#1|context}}
```

JS tree showing all (and only) the namespaces of the "private" namespace sorted by date creation. "private" is relative and refers to the private namespace under the page containing the indexmenu syntax.

```
{{indexmenu>private|js nopg dsort}}
```

## Metadata tag syntax

By default nodes on the same tree level are sorted by name (or by title/date if you use the tsort/dsort syntax), but you can also specify a custom sort number for every page inserting a metadata tag in the pages with this syntax:

```
{{indexmenu_n>N}}
```

Where N is a number. Then you need to use the "msort" option in your indexmenu tree syntax. If you have the show\_sort option enabled in the Configuration Manager, a notice is displayed to admins (only) on every page with this metadata tag (the text defaults to "Indexmenu sort number: N").

## Examples:

You can change the order of this tree containing a mix of standard and [useheading](#) pages:

```
-Root
|_don
|_Mirror sessions      (headline title of the ":mirror" page)
|_pachuco
|_At the radar station  (headline title of the ":radar" page)
|_van
|_vliet
```

in this way:

```
{{indexmenu>.:#1|msort}}
```



```
-Root
|_vliet          {{indexmenu_n>1}}
|_van            {{indexmenu_n>2}}
|_don            {{indexmenu_n>3}}
|_Mirror sessions (headline title of the ":mirror" page)
|_pachuco
|_At the radar station (headline title of the ":radar" page)
```

Pages without sort number, like the last three pages, are sorted by page name as default, but you can force a different sort:

```
{{indexmenu>..#1|tsort msort}}
```

```
-Root
|_vliet          {{indexmenu_n>1}}
|_van            {{indexmenu_n>2}}
|_don            {{indexmenu_n>3}}
|_At the radar station (headline title of the ":radar" page)
|_Mirror sessions (headline title of the ":mirror" page)
|_pachuco
```

## Video Share Plugin

Full documentation: <https://www.dokuwiki.org/plugin:vshare>

This plugin allows you to embed video players from various video sharing sites. New services can be added by just editing a config file. This is **not** for displaying local video files.

### Usage/Syntax

The basic syntax looks like this: `{{videosite>videoid?parameter1&parameter2|title}}`

- Where *videosite* is one of the identifiers listed in [Supported Services](#) chapter
- and *videoid* is the identifier of the video at the respective site
- The *parameters* are optional. You start these with a ? and separate more of them by a &. Look in [Parameters](#) chapter
- The title is optional as well. Look in [Examples](#) chapter
- The video can be aligned by adding spaces on the left or right inside the curly brackets (like in the image syntax). Look in [Examples](#) chapter

A toolbar button pops up a prompt where you can simply paste the full URL to the page of the video you want to embed. The plugin will then try to figure out the video ID by itself. For some services you may need to paste a special URL. See the table below.

### Parameters

When embedding a video you should add a size parameter.

You can either give it in the form:

- *widthxheight* like 500x300
- or use the keywords `small`, `medium` or `large`
- you can also use the keywords `full` or `half` to have the video adjust to the available screen width (either 100% or 50% width)

All additional parameters will be passed on as-is to the video service. Refer to their documentation for what is available. There are also hints in the table below.

## Examples

Display a YouTube Video:

```
{{youtube>L-WM8YxwqEU}}
```

Show a larger player:

```
{{youtube>L-WM8YxwqEU?large}}
```

Right-align the player:

```
{{ youtube>L-WM8YxwqEU}}
```

Show a small, centered player:

```
{{ youtube>L-WM8YxwqEU?small }}
```

Show a small, centered player with a title (look for right space!):

```
{{ youtube>L-WM8YxwqEU?small |Some funny video}}
```

Some other additional parameters are supported (depending on video service) as well:

```
{{youtube>L-WM8YxwqEU?small&start=30&end=45|A random segment of 15 seconds}}
```

## Supported Services

Copy paste the video url in the toolbar pop-up prompt to generate the syntax

Identifier	Website	Comments	Supported parameters
youtube	<a href="#">YouTube</a>		start, end, rel, autoplay
vimeo	<a href="#">Vimeo</a>		autoplay
slideshare	<a href="#">Slideshare</a>	paste the Wordpress shortcode	startSlide
dailymotion	<a href="#">Daily Motion</a>		start
twitchtv	<a href="#">Twitch.tv</a>		chapter_id, initial_time
archiveorg	<a href="#">Archive.org</a>		

Identifier	Website	Comments	Supported parameters
soundcloud	<a href="#">SoundCloud</a>		
niconico	<a href="#">NicoNico</a>		
break	<a href="#">Break</a>		
bitchute	<a href="#">BitChute</a>		
coub	<a href="#">Coub</a>		
odysee	<a href="#">Odysee LBRY</a>	paste the embed or download URL	
youku	<a href="#">Youku</a>	unclear if working	
bilibili	<a href="#">bili bili</a>		
msoffice		unclear if working	
msstream		unclear if working	

## Include Plugin

This is a handy plugin with which you can include another wiki page into the current one. Just including certain sections of a page or even whole namespaces is supported, too.

### Examples

`{{page>wiki:syntax#Tables}}` will include the section about tables of the syntax page.

`{{namespace>project_foo}}` will include all pages in the `project_foo` namespace.

`{{page>blog:mypage&tags&comments}}` will include the page `blog:mypage` and show the tags from the [tag](#) plugin and the number of comments from the [discussion](#) plugin. Both plugins need to be installed for this example.

`{{tagtopic>testtag}}` will include all pages with the tag `testtag`, the [tag](#) plugin needs to be installed for this example.

### Syntax

Simply enclose the ID of the page to be included in double curly brackets:

```
{{page>[id]&[flags]}}
{{section>[id]#[section]&[flags]}}
{{namespace>[namespace]#[section]&[flags]}}
{{tagtopic>[tag]&[flags]}}
```

<b>[id]</b>	page ID of the page to include; some <a href="#">macros</a> are possible; shortcuts are resolved (:, .., ...)	required
<b>[section]</b>	limits the included page to a specific section and its subsections	optional; default is the whole page, this can be used with namespace (if matches)
<b>[tag]</b>	include pages with tag topic tag, requires <a href="#">tag</a>	required
<b>[flags]</b>	flags delimited by &, see <a href="#">flags</a>	optional

The plugin offers four syntaxes, `{{page>...}}` , `{{section>...}}` , `{{namespace>...}}` and `{{tagtopic>...}}`.

Section is aimed more at including sections, page at including whole pages and namespace at including whole namespaces. Tagtopic includes all pages with a tagtopic tag.

## Configuration and Flags

The plugin can be configured in the DokuWiki configuration manager available in the admin menu. These settings also affect the [blog](#) plugin which uses the include plugin to generate the blog page. For most settings there are flags that allow to override the setting. Some features are only available as flag.

Configuration option	Flags	Description
<b>noheader</b>	noheader/ (show)header	Don't display the header of the inserted section
<b>firstseconly</b>	firstsec(tion)only/ fullpage	Display only the first section of the included page
<b>readmore</b>	readmore/noreadmore	Show "read more" link in case of firstsection only
<b>showtaglogos</b>	-	Show/hide an image for the first tag (if the page has tags)
<b>showfooter</b>	footer/nofooter	Show/hide page footer below the included page
<b>showlink</b>	link/nolink	Makes the first headline of a included page/section a link to the included page/section
<b>showpermalink</b>	permalink/ nopermalink	Show/hide a permalink to the included page in the page footer
<b>showdate</b>	date/nodate	Show/hide creation date of the page in the page footer
<b>showmdate</b>	mdate/nomdate	Show/hide modification date of the page in the page footer
<b>showuser</b>	user/nouser	Show/hide user name of the page creator in the page footer
<b>showcomments</b>	comments/nocomments	Show/hide number of comments in the page footer (requires the <a href="#">discussion</a> plugin)
<b>showlinkbacks</b>	linkbacks/nolinkbacks	Show/hide number of linkbacks in the page footer (requires the <a href="#">linkback</a> or <a href="#">backlinks2</a> plugin)
<b>showtags</b>	tags/notags	Show/hide tags in the page footer (requires the <a href="#">tag</a> plugin)
<b>showeditbtn</b>	editbtn or editbutton/noeditbtn or noeditbutton	Show/hide edit buttons (section edit buttons, edit button below the included page)
<b>doredirect</b>	redirect/noredirect	Redirect back to original page after an edit
<b>usernamepace</b>	-	Namespace for user pages (see showuser configuration) (default user)
<b>doindent</b>	indent/noindent	Indent included pages relative to the section of the page they get included in
<b>linkonly</b>	linkonly/nolinkonly or include_content	Display only a link instead of the whole page content

Configuration option	Flags	Description
<b>title</b>	title/notitle	Show the title instead of the page id
<b>pageexists</b>	pageexists/ nopageexists	Only list page ids of existing pages (see <a href="#">existlink</a> )
-	<a href="#">existlink</a>	Display a link and do so only if page page-id exists (combination of <a href="#">linkonly</a> and <a href="#">pageexists</a> )
<b>parlink</b>	parlink/noparlink	(Don't) put the link into a paragraph environment (for inline lists)
<b>order</b>	order=OPTION	Ordering criteria for namespace includes, possible options: page ID ( <a href="#">id</a> ), title ( <a href="#">title</a> ), date created ( <a href="#">created</a> ), date modified ( <a href="#">modified</a> ), <a href="#">indexmenu sort order</a> ( <a href="#">indexmenu</a> ), custom sort order using the <code>{{include_n&gt;[number]}}</code> on the pages that are included similar to the <a href="#">indexmenu</a> tags ( <a href="#">custom</a> ).
<b>rsort</b>	rsort/sort	Reverse the sort order in namespace includes.
<b>depth</b>	depth=DEPTH	The maximum depth of subnamespaces of which pages are included in namespace includes, default is 1 for only the specified namespace, 0 is for unlimited depth.
-	<a href="#">inline</a>	Don't close/open sections when including a page. This flag should be used when the include syntax is used inside other syntax elements like lists or tables or inside other plugin syntax.
-	<a href="#">beforeeach=ENTITY/</a> <a href="#">aftereach=ENTITY</a>	Display an <a href="#">entity</a> before/after each included page. The entity is printed outside the section/include environment, this is mainly for adding custom HTML code (when the text isn't recognized as entity it is directly displayed but escaped so you can't directly use HTML code here).
<b>safeindex</b>	-	Don't index metadata of included pages that are non-public. This can cause problems with other plugins that use the metadata index and can be safely disabled in wikis where the permissions of the included pages match the permissions of the parent pages.
-	<a href="#">exclude=/REGEX/</a>	Regular expression to exclude certain pages, will match on full page ID. E.g. to exclude <code>ns:page_name</code> use <code>/ns:page_name/</code> as value. Use a <a href="#">regex tester</a> to debug complicated patterns.

Examples:

```
{{page>concept&firstseconly&footer}}
{{page>mypage&noindent}}
{{namespace>myns&order=modified}}
{{namespace>myns&exclude=/myns:subns: .+|myns:page/}}
```

## Macros

Simple macros are possible to serve a page on a per user or per date base. These are:

<b>@USER@</b>	username
<b>@NAME@</b>	full name of user
<b>@GROUP@</b>	first group the user belongs to
<b>@YEAR@</b>	4-digit year
<b>@MONTH@</b>	2-digit month
<b>@WEEK@</b>	2-digit ISO week number
<b>@DAY@</b>	2-digit day
<b>@DATE&lt;expr&gt;@</b>	use a calculated date instead of today in date macros

<expr> in **@DATE<expr>@** can be one of:

<b>PYEAR</b>	previous year
<b>NYEAR</b>	next year
<b>PMONTH</b>	previous month
<b>NMONTH</b>	next month
<b>PWEEK</b>	previous week
<b>NWEEK</b>	next week
<b>YESTERDAY</b>	yesterday's date
<b>TOMORROW</b>	tomorrow's date

Examples:

```
{{page>@MONTH@:@DAY@:birthdays}}
```

includes the page birthdays in namespace <month>:<day>: eg. 10:15: birthdays for the 15th of october.

```
{{page>@USER@:message}}
```

includes the page message from the namespace <user> of the logged in user

```
{{page>foo@DATENWEEK@@YEAR@:@WEEK@}}
```

includes the page <weekno> from the namespace foo<year> with next week's date e.g. foo2012:01 for the 27th of december 2011

## (To)Do Plugin

The do plugin allows users to create simple tasks in wiki pages. Those tasks may be assigned to other users and have a due date. Tasks can be listed in pages as well.

## Syntax

There are two syntax elements.

### Task

```
<do USER DATE>TEXT</do>
```

Create a new task TEXT, optionally assign it to USER or mark it as due on DATE; there is a toolbar button for this as well.

Part	Details
USER	User id as accepted by current authentication backend
DATE	Date in format yyyy-mm-dd
TEXT	Description of task. Task texts needs to be <b>unique at a page</b> . Duplicates are seen as same task.

### Listing

```
{{dolist>NAMESPACE?id=ID&status=(DONE|UNDONE)&limit=COUNT&md5=MD5&user=ASSIGNEE&creator=CREATOR&from=YYYY-MM-DD&to=YYYY-MM-DD}}
```

List tasks in NAMESPACE with optional additional filtering

Part	Details
NAMESPACE	Namespace to search for tasks
id	Page to search for tasks
status	Can have value DONE or UNDONE. Case insensitive.
limit	Maximum number of items to display.
md5	Show only task with this MD5 value
user	User id of assigned person or @USER@
creator	User id of creator
from	Date YYYY-MM-DD
to	Date YYYY-MM-DD

1)

wer das Tag "eingefügt" (<ins>) benötigt. kann dies über Plugins realisieren. Siehe ganz unten!

2)

dies ist eine Fußnote

3)

eine zweite Fußnote

4)

ggf. mit einem "&" mit anderen Optionen wie der Größenangabe kombinieren

5)

Standardmäßig lässt sich [dieses, oft unerwünschte, Verhalten](#) momentan (13.03.2009) nicht für das komplette DokuWiki deaktivieren

6)

Konfigurationsoptionen [htmllok](#) bzw. [phpok](#)

7)

like tables, lists, new paragraphs, included files, etc.

<sup>8)</sup> <sup>9)</sup> <sup>10)</sup> <sup>11)</sup>  
, , ,

the namespace of the page displayed by a user who is navigating your site

From:

<https://wiki.loxberry.de/> - **LoxBerry Wiki - BEYOND THE LIMITS**

Permanent link:

<https://wiki.loxberry.de/wiki/syntax>

Last update: **2022/12/31 10:12**